

Order	Work	Parts	Category	Stich length (mm)
1	Print out paper pattern		Paper pattern	
2	Joint paper pattern with scotch tape. Cut off seam allowance line (dotted outline).		Paper pattern	
3	Iron fabric		Iron	
4	Fix paper pattern onto the backside of fabric with marking pins		Marking pins	
5	Cut off fabric along with dotted outline of paper pattern		Cut off	
6	Make crease of tri-fold on seam allowance of hem with iron. Do not sew yet.	Migoro	Iron	
7	* There is nothing to do for Miyatsu Guchi in case of mens'.	Migoro	-	
8	Make crease of tri-fold on both of paper pattern and fabric at cuffs of left & right sleeves with iron. Do not sew yet.	Sleeve	Iron	
9	At Base collar & Cover collar, make crease of seam allowance and center line with iron. The side, where paper pattern is set, is inside.	Collar	Iron	
10	Make a tri-fold crease at seam allowance of Okumi's hem with iron. Do not sew yet. Make a tri-fold crease at seam allowance of Okumi's Tsumashita (left & right edge under collar) with iron, take off paper pattern, and sew straight with sewing machine (or blind stitch)	Okumi	Iron, Sew straight	5
11	At left & right sleeves, take off paper pattern at - under sleeve - sleeve attachment - under sleeve attachment (That means everything except for cuff), and zig-zag sew them (or lock sewing machine).	Sleeve	Zig zag sew	
12	Take off paper pattern of sleeve attachment of Migoro (body), and zig-zag sew it (or lock sewing machine)	Migoro	Zig zag sew	
13	Fold back center line of Migoro (body), and knob-sew it (straight sew with sewing machine)	Migoro	Sew straight	2.5
14	Sew Okumi onto left & right front Migoro.	Okumi	Sew straight	2.5
15	Zig-zag sew 2 fabrics of seam allowance between front Migoro and Okumi (or lock sewing machine)	Okumi	Zig zag sew	
16	Put Migoro (body) and left & right sleeves in inside-out, and sew sleeve attachment with sewing machine (sew straight)	Sleeve	Sew straight	2.5
17	Fold Migoro (body) in half at shoulder line. Sew straight both of fabric and paper pattern at left & right underarms (under sleeve attachment) of Migoro (body) with sewing machine.	Migoro	Sew straight	2.5
18	Take off paper pattern at seam allowance of left & right Migoro's underarms (under sleeve attachment). And zig-zag sew two fabrics together (or lock sewing machine).	Migoro	Zig zag sew	
19	* There is nothing to do for Miyatsu Guchi in case of mens'.	Migoro	-	
20	Sew together left & right - under sleeve - under sleeve attachment with sewing machine	Sleeve	Sew straight	2.5
21	Take off paper pattern at left & right cuffs, and sew tri-folded cuffs with sewing machine (or blind stitch)	Sleeve	Sew straight	5

22	Take off all paper patterns from Migoro and Okumi. Fix seam allowance of Migoro's & Okumi's hem with marking pins Flip whole kimono to inside-out.	Migoro	Paper pattern	
23	Temporarily fix Base collar and Cover collar onto Migoro, and confirm collar's position and direction. The side, where collar width is narrow, is outside, and the side, where collar width is wider, is inside. And then open collar's inside, match collar's outside's seam allowance and Migoro's collar's seam allowance, and fix it with marking pins.	Collar	-	
24	Straight sew front side (side without paper pattern) of Base collar & Cover collar's outside (written on the paper pattern), onto Migoro's front side (side without paper pattern), with sewing machine. As for stitch length, it's 2.5mm around neck and it's 5mm at the other parts.	Collar	Sew straight	2.5 & 5
25	Straight sew Base collar's edges with sewing machine (or blind stitch)	Collar	Sew straight	5
26	Fold Base Collar & Cover collar along with the creases, fold the edges of Base collar to inside, and temporarily fix it with marking pins.	Collar	-	
27	Try it on once, and confirm if hem's line is straight and if the hem's height is correct. If it's wrong, make a crease with iron again.	Migoro	Iron	
28	Straight sew hem's seam allowance with sewing machine (or blind stitch)	Migoro	Sew straight	5
29	Sew together from Migoro's front side. Sew straight with sewing machine (or blind stitch). As for stitch length, it's 2.5mm around neck and it's 5mm at the other parts.	Collar	Sew straight	2.5 & 5